

Defoamer

RP-6560

Features and Advantages:

RP-6560 is a liquid defoamer containing 100 per cent active ingredients. It is suitable for use in various coatings and adhesives, such as printing pastes, leather and whip oils, and PVA, as well as in latex systems including styrene, butadiene, acrylic, polyvinyl chloride and its copolymers, ethylene/vinyl acetate, and water-soluble alkyd resins.

1. Excellent dynamic defoaming performance
2. Long-lasting anti-foaming effect
3. Good compatibility
4. Excellent high-temperature performance; suitable for use in environments above 60°C

Product parameter:

Appearance	Pale yellow to yellow liquid
Solid Content	>97%
Viscosity (25° C)	2,000 – 10,000 mPa • s
Water Solubility	Slightly soluble in water

Recommended dosage:

Inorganic pigments :0.2-1%

Usage:

It can be added directly to the system requiring defoaming.

Scope of application:

- Printing pastes, leather conditioning oil
- Water-based laminating adhesives
- Water-based adhesives
- High-viscosity coating systems
- Polyvinyl alcohol dissolution process

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; For more information, please visit: <https://www.rk-chem.com>

Packing:

20kg/drum.

Storage:

Store at room temperature (5° C – 40° C), away from direct sunlight. Best before 6 months.